

MONTAGGIO STANDARD STANDARD MOUNTING

CODICE DI ORDINAZIONE / ORDERING CODE

D240 P1 2 1 250

SINGOLA TARATURA / SINGLE SETTING = 10 ÷ 35 MPa
(SOLO PER LA VERSIONE "P1" / WITH VERSION "P1" ONLY)

DOPPIA e TRIPLA TARATURA / DOUBLE and TRIPLE SETTING = VEDI TABELLA / SEE TABLE
(SOLO PER LE VERSIONI "P2" - "M2" - "M3" / WITH VERSIONS "P2" - "M2" - "M3" ONLY)

PER LA SINGOLA E DOPPIA TARATURA L'ULTIMA LETTERA DEL CODICE DI ORDINAZIONE È SEMPRE Q / FOR SINGLE AND DOUBLE SETTING THE LAST LETTER OF THE ORDER CODE IS ALWAYS Q

TABELLA/TABLE	A = 100 MPa	F = 160 MPa	K = 210 MPa	Q = 260 MPa	V = 310 MPa
	B = 120 MPa	G = 170 MPa	L = 220 MPa	R = 270 MPa	W = 320 MPa
	C = 130 MPa	H = 180 MPa	M = 230 MPa	S = 280 MPa	X = 330 MPa
	D = 140 MPa	I = 190 MPa	N = 240 MPa	T = 290 MPa	Y = 340 MPa
	E = 150 MPa	J = 200 MPa	P = 250 MPa	U = 300 MPa	Z = 350 MPa

INCREMENTI DI PRESSIONE STANDARD STANDARD PRESSURE INCREASES				
Doppia taratura Double settings	+ 50 bar	+ 80 bar	+ 100 bar	+ 130 bar
Tripla taratura Triple settings	+ 80 + 130 bar	+ 80 + 100 bar	+ 50 + 130 bar	+ 100 + 100 bar

CONNESSIONI PNEUMATICHE / AIR CONNECTIONS

0 = 1/8" G

1 = RACCORDO T6 / T6 FITTING

2 = RACCORDO TUBO 1/4" / 1/4" FITTING

1 = P G 3/4" M

2 = P G 1" M

3 = P 1.5/16" (SAE 16)

P1 = SINGOLA TARATURA / SINGLE SETTING

P2 = DOPPIA TARATURA PNEUMATICA / DOUBLE PNEUMATIC SETTING

M2 = DOPPIA TARATURA MECCANICA / DOUBLE MECHANICAL SETTING


M3 = TRIPLA TARATURA MECCANICA / TRIPLE MECHANICAL SETTING

MODELLO / MODEL

CARATTERISTICHE TECNICHE / TECHNICAL SPECIFICATIONS

Portata nominale Flow rate	160-240 l/min	Temperatura fluido °C (t) Fluid temperature °C (t)	-25° + 80°C
Portata nominale - Massima in scarico Flow rate - Lowering max	250-300 l/min	Campo viscosità Viscosity range	12-100 cSt
Pressione massima di lavoro Max working pressure	350 bar	Filtrazione / Filtering ISO 4406 βx=75	20/17 25 μm
Pressione massima di picco (<0.1 s) Max peak pressure	400 bar	Peso Weight	8 kg
Pressione massima sul T T port max pressure	30 bar	Pressione pneumatica massima Max pneumatic pressure	4.5 - 12 bar

- Three way (pump, cylinder, tank) air operated control valve.
- Three positions:
 - hold,
 - tipping,
 - lowering.
- Variable descent speed with suitable air control.
- Relief valve setting up to 350 bar on port "P".
- Built-in check valve.



Mod. DM 240 P1

